



Price List w.e.f. 10th October 2025

BONTON CABLES (INDIA) PVT. LTD.

ISO:9001:2015, IATF:16949:2016, ISO:14001:2015, ISO:45001:2018, ISO:50001:2011, RoHS2 Compliant, Sedex/Smeta, G.C. Mark, Trusted Product, TUV For Solar & Fire Survival Cable

Plant-1 : A 115 RIICO Industrial Area, Phase-1, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)

Plant-2 : A 6A, Kaharani Industrial Area, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)

E Mail : marketing@bontoncablesindia.com, Phone No. - 8130299001

"BONTON" Brand Power Cables, Solid Aluminium Conductor Up To 10 sq.mm Balance Stranded Conductor, XLPE Insulated, Cores Laid Up, PVC Tape /Extruded Innersheathed for Multicore Cables, Armour (Aluminium Wire for Single Core Up To 70 sq.mm Balance Aluminium Strip, Galvanised Wire for Cables Upto 2x10 sq.mm, 4x6 sq.mm balance all Galvanised Steel Strip), Extruded PVC Type ST2 Sheathed, 650/1100V Grade as per IS:7098 (Part-1) 1988

ALUMINIUM ARMoured CABLE

Size (in sq.mm)	1 Core	2 Core	3 Core	3.5 Core	4 Core
6		285	310		370
10		360	400		510
16	230	410	430		540
25	303	435	570	665	710
35	365	540	725	805	920
50	450	700	945	1095	1225
70	580	940	1295	1470	1670
95	695	1160	1595	1845	2080
120	805	1385	2000	2315	2615
150	960	1705	2455	2740	3210
185	1175	2045	3040	3470	3950
240	1455	2715	3880	4355	5100
300	1790	3330	4795	5360	6290
400	2260	4320	6130	6845	7850
500	2815	5835	8215	9680	10855
630	3475	7180	10445	11860	14245
800	4275				
1000	5255				

EXTRA FOR SPECIAL CONSTRUCTION :

a) Round Wire Armouring	30%
- 2 x 16 sq.mm & above.	30%
-3 x 16 sq.mm & 3.5 x 25 sq.mm & Above	30%
-4 x 10 sq.mm & above	30%
- For Single Core 95 sq.mm & Above	30%
b) Stranding 10 sq.mm and Below	30%
c) Extruded PVC Innersheath Up 50	7.5%
Extruded PVC Innersheath 70 & Above	4.0%
d) HR PVC Insulation	17.5%
e) HR PVC Inner Sheath	7.5%
f) HR PVC Outer Sheath	7.5%
g) Oxygen Index (FR)	4.0%
h) PVC Insulated Cables	15%

FRLS-H Loading Factor			LSZH	
Cable Size	Inner Sheath	Outer Sheath Armoured	Inner Sheath	Outer Sheath
Power (Aluminium)				
Upto 16 sq.mm	15%	11.50%	22.5%	30%
25-50	11.50%	11.50%	18.00%	22.5%
70 & Above	7.5%	7.5%	22.5%	18.00%
Power Single Core (Aluminium)				
Upto 16 sq.mm	.-N.A.-.	15%	.-N.A.-.	37.5%
25-50	.-N.A.-.	15%	.-N.A.-.	30%
70 & Above	.-N.A.-.	11.50%	.-N.A.-.	26.00%

* The above rates are exclusive of GST which shall be charged extra

* This cancels all our previous Price Lists. This price List is subject to change without prior notice.

		Price List w.e.f. 10th October 2025			
		BONTON CABLES (INDIA) PVT. LTD.			
ISO:9001:2015, IATF:16949:2016, ISO:14001:2015, ISO:45001:2018, ISO:50001:2011, RoHS2 Compliant, Sedex/Smeta, G.C. Mark, Trusted Product, TUV For Solar & Fire Survival Cable		Plant-1 : A 115 RIICO Industrial Area, Phase-1, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)			
		Plant-2 : A 6A, Kaharani Industrial Area, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)			
		E Mail : marketing@bontoncablesindia.com, Phone No. - 8130299001			
"BONTON" Brand Power Cables, Solid Aluminium Conductor Up To 10 sq.mm Balance Stranded Conductor, XLPE Insulated, Cores Laid Up, PVC Tape /Extruded Innersheathed for Multicore Cables, Unarmoured, Extruded PVC Type ST2 Sheathed, 650/1100V Grade as per IS:7098 (Part-1) 1988					
ALUMINIUM UNARMoured CABLE					
Size (in sq.mm)	1 Core	2 Core	3 Core	3.5 Core	4 Core
6		185	215		265
10		265	295		345
16	130	270	335		440
25	185	345	485	615	650
35	240	455	645	700	775
50	305	570	795	945	1035
70	420	820	1145	1290	1485
95	545	975	1390	1650	1770
120	675	1215	1870	2125	2260
150	835	1510	2200	2485	2795
185	1035	1795	2770	3175	3460
240	1315	2355	3575	3890	4525
300	1625	2875	4385	5040	5510
400	2090	3590	5470	6295	7040
500	2630	4575	7745	8685	9820
630	3260	5825	9715	11525	13140
800	4065				
1000	5125				
EXTRA FOR SPECIAL CONSTRUCTION :					
a) Stranding 10 sq.mm and Below			10%		
b) Extruded PVC Innersheath Up 50			7.5%		
Extruded PVC Innersheath 70 & Above			4.0%		
c) HR PVC Insulation			17.5%		
d) HR PVC Inner Sheath			7.5%		
e) HR PVC Outer Sheath			7.5%		
f) Oxygen Index (FR)			4.0%		
g) PVC Insulated Cables			15%		
FRLS-H Loading Factor				LSZH	
Cable Size	Inner Sheath	Outer Sheath		Inner Sheath	Outer Sheath
Power (Aluminium)					
Upto 16 sq.mm	15%	11.50%		22%	30%
25-50	11.50%	11.50%		18.00%	22.5%
70 & Above	7.5%	7.5%		22.5%	18.00%
Power Single Core (Aluminium)					
Upto 16 sq.mm	.-N.A.-.	15%		.-N.A.-.	37.5%
25-50	.-N.A.-.	15%		.-N.A.-.	30%
70 & Above	.-N.A.-.	15%		.-N.A.-.	26.00%
* The above rates are exclusive of GST which shall be charged extra					
* This cancels all our previous Price Lists. This price List is subject to change without prior notice.					

Page - 2 of 3

BONTON CABLES (INDIA) PVT. LTD.

ISO:9001:2015, IATF:16949:2016, ISO:14001:2015,
 ISO:45001:2018, ISO:50001:2011, RoHS2
 Compliant, Sedex/Smeta, G.C. Mark, Trusted
 Product, TUV For Solar & Fire Survival Cable

Plant-1 : A 115 RIICO Industrial Area, Phase-1, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)

Plant-2 : A 6A, Kaharani Industrial Area, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)

E Mail : marketing@bontoncablesindia.com, Phone No. - 8130299001

"BONTON" Brand Power/Control Cables, Solid Copper Conductor Up To 6 sq.mm Balance Stranded Conductor, XLPE Insulated, Cores Laid Up, PVC Tape
 Innersheathed for Multicore Cables, Armoured (Galvanised Wire for Cables Upto 10 x 1.5 sq.mm, 8 x 2.5 sq.mm, 2 x 10 sq.mm, 3 x 10 sq.mm, 4 x 6 sq.mm Balance
 all Galvanised Steel Strip) Extruded PVC Type ST2 Sheathed, 650/1100V Grade as per IS:7098 (Part-1) 1988

COPPER ARMoured CABLE

Size (in sq.mm)	1 Core	2 Core	3 Core	3.5 Core	4 Core	5 Core
4		495	665		850	1245
6		700	960		1250	1810
10		1105	1555		2035	2755
16	945	1645	2275		3010	3955
25	1400	2700	3685	4415	4855	7045
35	1900	3700	5190	5925	6890	9545
50	2570	4830	7015	8260	9350	13065
70	3610	7175	10245	11860	13495	20555
95	4795		14205	16265	18745	
120	6035		17415	21390	23360	
150	7505		22150	25875	29675	
185	9230		28155	32945	37610	
240	11855		36575	42520	48515	
300	14780		46095	53310	61695	
400	19325		59205	67375	82475	
500	24430					
630	30775					

Number of Cores	1.5	2.5	Number of Cores	1.5	2.5
2	250	355	14	1170	1835
3	320	460	16	1305	2085
4	395	595	19	1550	2455
5	480	730	24	1940	3075
6	575	860	27	2155	3450
7	630	970	30	2405	4150
8	810	1180	37	3120	4845
10	920	1360	44	3645	5660
12	1020	1580	61	5365	8205

EXTRA FOR SPECIAL CONSTRUCTION :

A) Tinning	3%
B) Stranding (Upto 6 sq.mm)	4%
C) Extruded Inner Sheath	4.0%
D) Round Wire Armouring	
1 Core x 95 sq.mm & Above	9.0%
1.5 sq.mm - 12 Core & Above	18%
2.5 sq.mm - 9 Core & Above	18%
10 sq.mm - 4 Core & Above	18%
16 sq.mm - 2 Core & Above	18%
16 sq.mm - 3 Core & Above	18%
E) OXYGEN INDEX (FR)	4.0%
F) HR PVC Insulation	17.5%
HR I/S & O/S	7.5% EACH
G) FRLS Loading Power Cable (upto 6 sq.mm)	11.5%
FRLS Loading Power Cable (10 sq.mm & Above)	6%
H) PVC Insulated Cables	15%

FRLS-H Loading Factor - Control Cable			LSZH	
Cores	Inner Sheath	Outer Sheath Armoured	Inner Sheath	Outer Sheath
2 to 4 Core	7.5%	9%	22.5%	22.5%
5 to 10 Core	7.5%	6%	22.5%	22.5%
12 & Above	7.5%	6%	18.00%	18.00%

* As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price list are only for guide-lines and are as per market convention. It may vary within the prescribed limit of IS:8130-1994, with related classes and tables:

* The above rates are exclusive of GST which shall be charged extra

* This cancels all our previous Price Lists. This price List is subject to change without prior notice.

		Price List w.e.f. 10th October 2025				
		BONTON CABLES (INDIA) PVT. LTD.				
ISO:9001:2015, IATF:16949:2016, ISO:14001:2015, ISO:45001:2018, ISO:50001:2011, RoHS2 Compliant, Sedex/Smeta, G.C. Mark, Trusted Product, TUV For Solar & Fire Survival Cable		Plant-1 : A 115 RIICO Industrial Area, Phase-1, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)				
		Plant-2 : A 6A, Kaharani Industrial Area, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)				
		E Mail : marketing@bontoncablesindia.com, Phone No. - 8130299001				
"BONTON" Brand Power/Control Cables, Solid Copper Conductor Up To 6 sq.mm Balance Stranded Conductor, XLPE Insulated, Cores Laid Up, PVC Tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured Extruded PVC Type ST2 Sheathed, 650/1100V Grade as per IS:7098 (Part-1) 1988						
COPPER UNARMOURED CABLE						
Size (in sq.mm)	1 Core	2 Core	3 Core	3.5 Core	4 Core	
4		420	600		745	
6		615	885		1095	
10		1070	1505		1790	
16	790	1505	2185		2805	
25	1270	2505	3485	4150	4560	
35	1755	3470	4855	5590	6540	
50	2405	4760	6600	7905	8740	
70	3425	6790	9725	11405	12915	
95	4670		13910	16190	18110	
120	5885		16285	20705	23185	
150	7355		21805	25190	28980	
185	9030		26915	31465	35885	
240	11660					
300	14545					
400	19115					
500	24155					
630	30365					
Number of Cores	1.5	2.5		Number of Cores	1.5	2.5
2	195	300		14	970	1750
3	280	415		16	1160	2005
4	355	560		19	1385	2370
5	435	700		24	1755	2995
6	525	830		27	1940	3325
7	590	950		30	2305	3940
8	720	1075		37	2985	4725
10	860	1235		44	3490	5635
12	920	1510		61	5105	7755
EXTRA FOR SPECIAL CONSTRUCTION :						
A) Tinning			3%			
B) Stranding (Upto 6 sq.mm)			4%			
C) Extruded Inner Sheath			4%			
E) OXYGEN INDEX (FR)			4%			
F) HR PVC Insulation			17.5%			
HR I/S & O/S			7.5% EACH			
G) FRLS Loading Power Cable (upto 6 sq.mm)			11.5%			
FRLS Loading Power Cable (10 sq.mm & Above)			6%			
H) PVC Insulated Cables			15%			
FRLS-H Loading Factor - Control Cable				LSZH		
Cores	Inner Sheath	Outer Sheath		Inner Sheath	Outer Sheath	
2 to 4 Core	7.5%	9%		22.50%	22.5%	
5 to 10 Core	7.5%	6%		22.50%	22.5%	
12 & Above	7.5%	6%		18.00%	18.00%	
* As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price list are only for guide-lines and are as per market convention. It may vary within the prescribed limit of IS:8130-1994, with related classes and tables:						
* The above rates are exclusive of GST which shall be charged extra						
* This cancels all our previous Price Lists. This price List is subject to change without prior notice.						
Page - 3 of 3						