

BONTON CABLES (INDIA) PVT. LTD.

ISO:9001:2015, IATF:16949:2016
ISO:14001:2015, ISO:45001:2018,
ISO:50001:2011, RoHS2 Compliant,
Sedex/Smeta, G.C. Mark, Trusted Product,
TUV For Fire Survival Cable

Plant-1 : A 115 RIICO Industrial Area, Phase-1, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)

Plant-2 : A 6A, Kaharani Industrial Area, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)

E Mail : marketing@bontoncablesindia.com, Phone No. - 8130299001

Bonton Single Core Copper Conductor PVC Cables (Unsheathed)-HRFR

1100V Grade Conforming to IS:694

Nominal Area of Conductor sq.mm	HRFR PVC		Std. Pkg. of Coil in Master Carton	HRFR PVC In Project Packing	
	PartNo.	MRP (90 Mtr. Box)		PartNo.	MRP (180 Mtr. Coil)
0.75	110266N	1710	20	110266P	4340
1	110267N	2195	20	110267P	5210
1.5	110268N	3245	16	110268P	7640
2.5	110269N	5235	12	110269P	12480
4	110270N	7695	8	110270P	18960
6	110271N	11625	4	110271P	28335

Standard Packing : 90mtr. In Carton* Project Packing: 180 mtrs. Polywrapped

Colour Available : Red, Yellow, Blue, Black, White, Green & Grey

Bonton Single Core Copper Conductor PVC Insulated Cables (Unsheathed) - FRLS(H)

1100V Grade Conforming to IS:694

Nominal Area of Conductor sq.mm	FRLS(H) PVC		Std. Pkg. of Coil in Master Carton	FRLS(H) PVC in Project Packing	
	Part No.	MRP (90 Mtr. Box)		Part No.	MRP (180 Mtr. Coil)
0.75	110266NLS	1795	20	110266PLS	4555
1	110267NLS	2305	20	110267PLS	5470
1.5	110268NLS	3405	16	110268PLS	8025
2.5	110269NLS	5495	12	110269PLS	13105
4	110270NLS	8080	4	110270PLS	19910
6	110271NLS	12205	4	110271PLS	29750

Standard Packing : 90mtr. In Carton * Project Packing : 180 mtrs. Polywrapped

Colour Available : Red, Yellow, Blue, Black, White, Green & Grey

Bonton Single Core Copper Conductor ZHFR Insulated Cables - ZHFR

1100V Grade Conforming to IS:17048 (Unsheathed)

Nominal Area of Conductor sq.mm	ZHFR		Std. Pkg. of Coil in Master Carton	ZHFR in Project Packing	
	Part No.	MRP (90 Mtr. Box)		Part No.	MRP (180 Mtr. Coil)
0.75	110267NZ	2205	20	110267PZ	4860
1	110267NZ	2875	20	110267PZ	5825
1.5	110268NZ	4215	16	110268PZ	8570
2.5	110269NZ	6835	12	110269PZ	13995
4	110270NZ	9980	4	110270PZ	21225
6	110271NZ	15120	4	110271PZ	31720

Standard Packing for ZHFR : 90mtr. In Carton * Project Packing : 180 mtrs. Polywrapped

Colour Available : Red, Yellow, Blue, Black & Green

Bonton Single Core Copper Conductor PVC Cables (Unsheathed) - HRFR

1100V Grade Conforming to IS:694

Nominal Area of Conductor sq.mm	HRFR PVC		Nominal area of Conductor sq.mm	HRFR PVC	
	Part No.	MRP (100 mtr.)		Part No.	MRP (100 mtr.)
10	110272H	27680	120	110279H	325120
16	110273H	43075	150	110280H	406960
25	110274H	67765	185	110281H	506355
35	110275H	94845	240	110282H	660975
50	110276H	135295	300	110283H	826925
70	110277H	191140	400	110284H	1101820
95	110278H	252205	500	110285H	1378375

Standard Packing : 100 mtrs. Coils

Colour available : Red, Yellow, Blue, Black & Green

* FRLS(H) insulation: 5% Extra

* HFLS (Halogen Free Insulation) : 12% Extra

BONTON CABLES (INDIA) PVT. LTD.

ISO:9001:2015, IATF:16949:2016
ISO:14001:2015, ISO:45001:2018,
ISO:50001:2011, RoHS2 Compliant,
Sedex/Smeta, G.C. Mark, Trusted Product,
TUV For Fire Survival Cable

Plant-1 : A 115 RIICO Industrial Area, Phase-1, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)

Plant-2 : A 6A, Kaharani Industrial Area, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)

E Mail : marketing@bontoncablesindia.com, Phone No. - 8130299001

Bonton Single Core Copper Conductor PVC Cables (Unsheathed) - HRFR & FRLSH

1100V Grade Conforming to IS : 694

Nominal Area of Conductor sq.mm	HRFR PVC in Project Packing		FRLSH PVC in Project Packing	
	Part No.	MRP (200 mtr. Coil)	Part No.	MRP (200 Mtr. Coil)
0.5	110265 T	3295	110265 TLS	3460
0.75	110266 T	4295	110266 TLS	4510
1	110267 T	5665	110267 TLS	5945
1.5	110268 T	8300	110268 TLS	8715
2.5	110269 T	13555	110269 TLS	14230
4	110270 T	20565	110270 TLS	21595
6	110271 T	30735	110271 TLS	32270

Colour available : Red, Yellow, Blue, Black, White, Green & Grey

Bonton Jelly Flooded Aluminium Foil & Aluminium Wire Braided Co-Axial Cables

Size	Part No.	100 Meter Unarmoured	305 Meter Unarmoured	1000 Meter Armoured
RG 59	110086	3985	11950	
RG 6	110087	5010	15015	142560
RG 11	110088	10885	32935	217790

Bonton PVC insulated Telephone Cables for Indoor application conforming to TEC Specification G/WIR06/02

No. of Pair (0.40mm)	Part No.	MRP - 100 Mtr. (0.40 mm)	No. of Pair (0.50 mm)	Part No.	MRP - 100 Mtr. (0.50 mm)	No. of Pair (0.61 mm)	Part No.	MRP - 100 Mtr. (0.61 mm)
1	110082	1370	1	110091	1805	1	110101	2660
2	110083	2375	2	110092	3010	2	110102	5060
3	110084	3065	3	110093	4535	3	110103	7565
4	110085	3940	4	110094	5995	4	110104	10205
5	110086	5095	5	110095	7135	5	110105	12665
10	110087	10305	10	110096	14565	10	110106	26250
20	110088	20595	20	110097	28980	20	110107	51350
50	110089	-	50	110098	70685	50	110108	125385
100	110090	-	100	110099	148675	100	110109	250850

Bonton Multi Core Copper Conductor PVC Cables (Sheathed) - FR

1100V Grade Conforming to IS : 694

Nominal Area of Conductor sq.mm	Part No.	2 Core	Part No.	3 Core	Part No.	4 Core	Part No.	5 Core
0.5	110308 2C	4135	110308 3C	5670	110308 4C	7255	110308 5C	9105
0.75	110309 2C	5525	110309 3C	7670	110309 4C	9865	110309 5C	12910
1	110310 2C	7015	110310 3C	9765	110310 4C	12620	110310 5C	16710
1.5	110311 2C	9565	110311 3C	13715	110311 4C	17770	110311 5C	22660
2.5	110312 2C	15740	110312 3C	21710	110312 4C	29335	110312 5C	37215
4	110313 2C	23140	110313 3C	33410	110313 4C	44375	110313 5C	58575
6	110314 2C	34130	110314 3C	49150	110314 4C	65265	110314 5C	86260
10	110315 2C	58225	110315 3C	85665	110315 4C	113230	110315 5C	148775
16	110316 2C	92110	110316 3C	134580	110316 4C	177775	110316 5C	228240
25	110317 2C	153430	110317 3C	223340	110317 4C	291710	110317 5C	414955
35	110318 2C	213675	110318 3C	310325	110318 4C	407800	110318 5C	568500
50	110319 2C	303290	110319 3C	442050	110319 4C	583660	110319 5C	822755
70	110320 2C	430940	110320 3C	613140	110320 4C	810465	110320 5C	1124970

Standard Packing : 100 mtrs. Coil

* FRLS(H) insulation : 5% Extra

* HFLS (Halogen Free Insulation) : 12% Extra

BONTON CABLES (INDIA) PVT. LTD.

ISO:9001:2015, IATF:16949:2016
ISO:14001:2015, ISO:45001:2018,
ISO:50001:2011, RoHS2 Compliant,
Sedex/Smeta, G.C. Mark, Trusted Product,
TUV For Fire Survival Cable

Plant-1 : A 115 RIICO Industrial Area, Phase-1, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)

Plant-2 : A 6A, Kaharani Industrial Area, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)

E Mail : marketing@bontoncablesindia.com, Phone No. - 8130299001

Bonton PVC Insulated and Sheathed 3 Core Flat Submersible Cable

1100V grade conforming to IS : 694/1990

Nominal area of Conductor sq.mm	Part Number	MRP - Per 100 Mtrs.
1.5	110311 3C FT	15055
2.5	110312 3C FT	25035
4	110313 3C FT	35850
6	110314 3C FT	52100
10	110315 3C FT	87940
16	110316 3C FT	136145
25	110317 3C FT	219225
35	110318 3C FT	305125

Bonton PVC Insulated and sheathed 4 Pair Twisted LAN Cable

Size	MRP 305 Meter
CAT 6	18690

Flexible Bare Copper Conductor PVC Insulated Overall Aluminium Mylar Tape Shielded along with ATC Drain wire PVC Outer Sheath Aluminium Mylar Tape Wires / Cables (100 Mtr Coil)

Core	0.5 sq.mm	0.75 sq.mm	1.0 sq.mm	1.5 sq.mm	2.5 sq.mm
2	6925	8865	10630	13845	21655
3	8575	11665	14070	18730	29945
4	10625	14070	18035	25295	37825
5	13115	17545	21355	29235	47835
6	15150	19915	24925	35190	57265
7	16465	23375	28990	39605	67765
8	18730	25295	32215	44260	75635
10	22190	31255	39605	54755	92455
12	26250	36625	46765	64905	113465
14	30540	42830	54035	74690	
16	34595	48075	60840	86130	
19	39610	57260	71935	100220	
24	49150	70275	88995	128015	

Note : 3% Extra Charges for Drum packing

FIRE SURVIVAL CABLE

Bonton Multicore High Proformance Silicon Rubber (HPSR) Insulated LSZH Sheathed Fire Survival Cable - TUV Certified Cable

Test as per BS:6387 C.W.Z.

Size	Part No.	MRP - Per Mtr (Un-armoured)	MRP - Per Mtr (Armoured)
2 Core x 1.5 sq.mm	110331	390	460
3 Core x 1.5 sq.mm	110332	480	550
2 Core x 2.5 sq.mm	110333	530	575
3 Core x 2.5 sq.mm	110334	630	710

Bonton MICA Tape Multicore XLPE Insulated LSZH sheathed Copper Armoured Fire Survival Cable - TUV Certified Cable

Test as per BS6387 C.W.Z.

Size	Part No.	MRP- Per Mtr.
2 Core x 1.5 sq.mm	110341	345
3 Core x 1.5 sq.mm	110342	430
2 Core x 2.5 sq.mm	110343	480
3 Core x 2.5 sq.mm	110344	595

Terms & Conditions : -

1. GST @ 18% Extra on Copper Flexible PVC Insulated Wire & PVC Insulated/Sheathed Cable (HSN Code 85446020)
2. Order are accepted subject to availability of stocks.
3. Conductor Resistance as per IS 694 is the governing criteria.